
Errata: CS4297A Rev. C

(Reference CS4297A_DS318PP6 Data Sheet dated March '06)

1. When the PC_BEEP bypass is active (RESET# actively asserted and BCFG pin floating) the input impedance for the PC_BEEP input can be lower than the specified minimum of 10 k Ω (approximately 1 k Ω).
2. The CS4297A requires a minimum SYNC pulse width of 1.13 μ s in the absence of BIT_CLK for a warm reset to occur. AC '97 version 2.1 requires SYNC to be asserted for a minimum of only 1.0 μ s.

Note: This requirement refers to the behavior of SYNC during warm reset only. During normal operation, SYNC is asserted for the entire period of slot 0 (the tag phase), which is 16 cycles of BIT_CLK.

3. SDATA_IN does not meet the AC '97 specification of driving a 47.5 pF capacitive load within the rise time constraints of $2 \text{ ns} \leq T_{\text{rise}} \leq 6 \text{ ns}$. However, even at maximum capacitive loading, the codec provides sufficient SDATA_IN data setup margin to prevent any functional issues.

Workaround Solution - Minimize SDATA_IN trace length during board layout, and keep the total capacitive loading to 22 pF or less.

Contacting Cirrus Logic Support

For all product questions and inquiries, contact a Cirrus Logic Sales Representative.

To find the one nearest you, go to <http://www.cirrus.com>